



- [MarkNet Home](#)
- [KLR650](#)
- [Homepage](#)
- [Computer Stuff](#)
- [Contact](#)

Links

[Miscellaneous Info](#)

[Grease 101](#)

Technical Articles

[A1 Brochure](#)

[Conversions](#)

[KLR650 FAQ](#)

Forms

- [Maintenance Log](#)
- [Shim Record Chart](#)

Pictures

[Corbin Saddle](#)

Procedures in PDF

Procedures

- [12v Waterproof Outlet](#)
- [Acerbis Disk Installation](#)
- [Balancer Adjustment](#)
- [Brake Pads](#)
- [Cam Chain Timing](#)
- [Carb Rain T-Mod](#)
- [Decalifornication](#)
- [Dooickey Upgrade](#)
- [Easy Lift](#)
- [Fork Oil Change](#)

This is a hobby website dedicated to the Kawasaki KLR650 motorcycle. I make no claim concerning the accuracy of the procedures, nor do I guarantee the success of any work done using them. All users of the material found here are advised that there is no real or implied warranty associated in any way with the website content, and that all content available here is for use at your own risk.

Copyright © 2001 Mark's KLR Pages

All Rights Reserved

No copying or other redistribution by any method will be permitted without my express written permission.

J.C. WHITNEY TRUNK



- Horn Upgrade
- Hydraulic Clutch
- JC Whitney Trunk
- Oil Screen Cleaning
- Radiator Cooling Mod
- Ramp Loading
- Safety Switch Bypass
- Shark Fin Installation
- Shim Storage Box
- Shim Value Table
- SuperBrace
- Swingarm Maint
- Torque Values
- Tube Valve Tools
- TWC Acc Fuse Kit
- TWC Fuse Relocation Kit
- Valve Adjustment
- Vista-Cruise Lock
- Water Pump Seals
- Wheel Alignment



Computer Guides
for
Geezers of Any Age!

J.C. Whitney offers two very reasonably priced trunks, the one that I have is pictured above.

The One That I Have

Or This One

I would have been able to use only two existing holes for the mounting plate, and that would have put the trunk in a position that was too far forward for my wife to ride comfortably with me, and would *probably* have been too far forward for me and my waterproof duffel that I net on the back of the seat up against the trunk.

I didn't like the bolts that came with the trunk, and couldn't get them to sit low enough to not interfere with easy removal and installation of the trunk onto the mounting plate. I got funnel-headed stainless bolts from a hardware store as a substitute. They nicely sit down into the plate.

I positioned the mounting plate just far enough back so that I could still use the stock tool kit box.

The pictures should show how I placed the bolts, and that I just cut off the bolt ends to the right length so they'd fit between the rack bottom and the fender top. I used a countersinking router bit in my drill to make sure the bolts sat as flush as possible - that probably wasn't necessary.



The picture above should give you a better idea of the bolts that *I* found to work best for installing the trunk mounting plate - even better than the ones supplied. This is just a standard (not metric) stainless bolt with a funnel head that fits perfectly into the pre-drilled mounting plate bolt holes.



The picture above shows the mounting plate of the trunk being measured from the front-most corner of the KLR rack to the flat jutting out part of the mounting plate. This measurement is 3 ⁷/₈"



The picture above shows the back end of the stock KLR rack being measured to the middle-end of the mounting plate. This measurement is 3 3/4"





The underside of the rack / mounting plate. I used some blue loctite along with the split washers to make sure that everything stayed in place, and wasn't rattled loose.

From what I've heard, both JCW trunk styles, (see the links above), now come with straps, although I'm not sure if they have to be used in the mounting or not.



The above picture shows the trunk as it sits mounted on the plate. There's access to the stock tool kit, plenty of room for a passenger to sit comfortably, or a large duffel to be netted on the saddle up against the back of the trunk.